

TRANSFERWEAR

COLOUR LASER COPIER PAPER INFO

TPL 300

Application Instructions

1. Reverse (flip or mirror) the image before printing.
2. Load the transfer paper so that the blank side receives the image.
3. Fan the sheets of the transfer paper on all four sides to reduce static charge.
4. Preheat the heat press to 375°F / 190°C.
5. Trim away any unprinted area around your image.
6. Choose a white or light colored substrate made of 100% cotton, cotton/poly blend or 100% polyester.
7. Transferring onto Garment.
8. Place wrinkle free garment onto the press pad.
9. Place transfer image side down.
10. Heat press for 15 seconds with medium to heavy pressure.
11. Peel hot immediately.

Garment Care / Washing

- Turn garment inside out before washing.
- Machine wash warm or cold.
- Mild colour safe detergent (no bleach).
- Dry in dryer inside out on a low setting.
- If garment needs ironing, do not iron directly on the transfer.

Tips & Notes

- Room temperature should be about 75°.
- Paper should acclimate 12-24 hour prior to use.
- Warm up your copier.
- Preheat your press.
- Use a humidifier or dehumidifier to achieve a relative humidity of approximately 40%.
- Your CLC should be checked every 30,000 copies.
- Copies should run on its own circuits.
- Have toner waste boxes emptied at least once a year.
- If colour is off after adjusting the toner and saturation levels, the starter may need replacing.
- When using Transferwear products, remember they require less toner than ordinary papers.
- Toners darken with heat: therefore the image on the transfer should be more lighter.
- Clean the glass on your CLC often.
- For every 50 sheets of transfer paper, run a sheet of Laser Cleaning paper through the CLC.
- Do not store paper in the tray inside the machine, but the paper needs to be kept in the same area as the copier.
- All copyright laws apply to use of the TRANSFERWEAR paper.
- Manufacturer and seller are not responsible for damaged caused by misuse of this paper.

Storage & Handling

For best results, condition Transferwear CLC paper in your location for 12-24 hours before use. Store the paper in a cool, dry area and do not remove the packaging until you are ready to use. Put any unused paper back into the resealable bag. This will help improve the quality of your image and reduce copier jams.

ASIA WINNER SDN BHD

NO 7, JALAN BUDI TENGAH 1, TAMAN WAWASAN PERINDUSTRIAN, 83000 BATU PAHAT, JOHOR, MALAYSIA.

Hunting Line : 607-428 9888 (5 LINES)

Fax : 607-428 9222

Email : info@asiawinner.com.my

Website: www.asiawinner.com.my